RESIDENTIAL

WST-NCX48-BW

N-TYPE BIFACIAL GLASS-GLASS SERIES

470W



30 years product warranty
30 years linear performance
-1 % 1st-year degradation
-0.40 % annual power degradation
>87.4 % of linear performance after 30 years
Applicable to front-side power at STC only

WINAICO
Solar for Experts.

www.winaico.com.au

MECHANICAL DATA


Cell	Monocrystalline, N-type, bifacial
Quantity and wiring of cells	96 (6 strings x 16 cells)
Bifaciality	Up to 80%
Dimensions	1,762 x 1,134 x 35 mm
Weight	25 kg (55.1 lbs)
Front-side glass	2.0 mm, semi-tempered solar glass with anti-reflective coating
Back-side glass	2.0 mm, semi-tempered solar glass, partially black printed
Frame	Black anodised aluminium
Junction box	IP68, 3 bypass diodes
Connector type	Stäubli Electrical Connectors AG PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy
Cable length (IEC/UL)	Cable x 2 1,200 mm / 4 mm²
Fire safety class[1] (IEC61730)	Class C
Protection class (IEC 61140)	II


OPERATING CONDITION

Operating temperature	–40 °C to +85 °C / –40 °F to +185 °F
Module [T98] $_{MAX}$	70°C
Maximum system voltage IEC	1,500 VDC
Maximum series fuse	30 A*1
Maximum design load (push/pull)	+3,600 Pa / -1,600 Pa
Maximum test load (push/pull)*2	+5,400 Pa / -2,400 Pa
Nominal module operating temperature NMOT	42 ± 2°C
Temperature coefficient of P_{MAX}	-0.28%/°C
Temperature coefficient of V_{OC}	-0.23%/°C
Temperature coefficient of I_{SC}	0.043%/°C


*1. The installation of additional blocking diodes or fuses is necessary with the parallel connection of module strings.
*2. Depending on the type of installation according to the installation instructions.

DIMENSIONS






Frame cross section



Mounting slot

PACKAGING




1,800 mm	1,140 mm	1,267 mm	31 modules	822 kg	26 pallets

ELECTRICAL DATA

Module type: **WST-470NCX48-BW**


Electrical data		STC[2]	NMOT[3]	BNPI[4]	
Nominal performance	P_{MAX}	470	358	515	Wp
Voltage at maximum performance	V_{MP}	30.79	29.10	30.79	V
Current at maximum performance	I_{MP}	15.27	12.31	16.73	A
Open circuit voltage	V_{OC}	35.90	34.36	35.90	V
Short circuit current	I_{SC}	15.93	13.17	18.08	A
BSI: 1000 W/m² front / 300 W/m² rear irradiance	I_{SC}	20.22			A
Maximum power bifaciality coefficient	ϕP_{MAX}	80±10			%
Open circuit current bifaciality coefficient	ϕV_{OC}	95±5			%
Short circuit current bifaciality coefficient	ϕI_{SC}	80±10			%
Module efficiency		23.5			%
Bifacial gain[5] *Depending on irradiation conditions	10 % Pmpp	517 (+47)			W
	15 % Pmpp	541 (+71)			W
	20 % Pmpp	564 (+94)			W
Power tolerance		0~+5			W

WINAICO PERFORMANCE GUARANTEE



Based on front-side power at STC

CHARACTERISTIC CURVES



PRODUCT AND QUALITY CERTIFICATES

IEC 61215:2021, IEC 61730:2023
IEC 61701 Salt Mist Resistance
IEC 62716 Ammonia Resistance
IEC 61215-2 Hail Storm Resistance (45mm at ~30.7m/s)
IEC TS 62804-1 Anti-PID

ISO 9001 Quality Management System
ISO 45001 Occupational Health and Safety Management System
ISO 14001 Environment Management System
SA 8000 Social Accountability

1. The fire safety test methods according to IEC 61730-2, Fire Tests of Roof Coverings.
2. Electrical data applies under standard test conditions (STC): solar radiation 1,000 W/m2 with light spectrum AM 1.5, with cell temperature 25 °C. Measurement tolerance of Pmax: ±3%; Voc: ±3%; Isc: ±3% at STC.
3. Electrical data applies under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.
4. BNPI: The front side 1,000 W/m² solar irradiance and rear 135 W/m². NMOT/BNPI: Measurement tolerance of Pmax: ±3%; Voc: ±3%; Isc: ±3%.
5. The additional power gain from the rear side depends on the irradiance conditions at the installation site and the mounting situation.at the installation site and the mounting situation.

WINAICO Australia Pty Ltd
Tel + 61 2 8091 2771
australia@winaico.com
www.winaico.com.au
3/393 George Street, Sydney NSW 2000, Australia

Win Win Precision Technology Co., Ltd
Tel + 886 3 568 8699 · info@w-win.com.tw
www.wwpt.com.tw · www.winaico.com
4F., No. 180, Sec. 2, Gongdao 5th Rd., East Dist.,
Hsinchu City 300, Taiwan R.O.C.
Made in China

WINAICO Solar for Experts.

WINAICO is a trademark of Win Win Precision Technology Co., Ltd.

Specifications included in this datasheet are subject to change without notice. WST-470NCX48-BW_AUS_CEC.0826