coolcept fleX XL

StecaGrid 4213, StecaGrid 5513, StecaGrid 7013, StecaGrid 8513, StecaGrid 10013

3 ph



It's simply flexible, powerful and efficient

Thanks to its broad input voltage range and different power classes, the coolcept fleX XL is suited for almost all forms of equipment. The coolcept fleX XL provides a product range of 4.2 – 10 kW and contains two MPP trackers. This wide voltage and current range makes any design possible without any issues. This means that the highest yields can be achieved with innovative shade management.

Through the high flexibility of the coolcept fleX XL almost any photovoltaics system can be fitted with this Steca inverter.

Simply more communicative

The large number of communication interfaces renders further components for monitoring unnecessary. The coolcept fleX XL also supports the advanced technologies in the smart home sector.

- Display, data logger, system monitoring, network and control interfaces integrated as standard
- Local and mobile system monitoring via PC, smartphone or tablet
- Free solar portal - Steca sunCloud - For monitoring the PV system .br />- Commissioning, configuration and display of graphically prepared yield data directly via the inverter display
- Optional connection of an external energy meter
- EEBus and Sunspec for SmartHome integration

Simply more comfortable

The design of the coolcept fleX XL is geared towards convenient, safe installation and operation.

- Ergonomic grip rails for easy handling
- Front-mounted robust disconnector with easy-to-read switching status
- Safe installation thanks to clear separate terminal compartment and protected power electronics
- Tool-free installation of the PV plug thanks to Phoenix SUNCLIX